

SONIX GSB BACKLIGHT SERIES



FEATURES :

- » Constant Voltage Driven.
Up to 80% energy saving.
- » Long service life up to 40000 hrs.
- » Epistar (99.9%) Gold Thread,
Pure Copper, Bracket coated with silver LED.
- » High Pressure Ultrasonic with
100% Poly Carbonate Casing.
- » Special Lens Design (160°) Degree
beaming angle with equal light.
- » Easy Installation with Double-Sided
Quality tape for assured installation.
- » High luminous efficiency up to 110 lm/W.
- » IP 65 Waterproof.

Technical Specification

MODEL:	SONIX 1 LED DC:	SONIX 1 LED AC:
COLOR :	Cool White/Warm White	Cool White/Warm White
CCT :	10000K/3000K	10000K/3000K
POWER/W :	3 Watts	3 Watts
Operating Power :	DC - 12V	AC - 220V
CRI :	80 RA	80 RA
PCB DETAILS :	1.2mm Alu. With 35mic. Copp.	1.2mm Alu. With 35mic. Copp.
SIZE :	52mm*42mm*13mm	52mm*42mm*13mm
LENS DET :	160 DEGREE	160 DEGREE
TEMP :	0 TO 70	0 TO 70
QTY. STRING :	14 Nos.	14 Nos.
Series Distance :	9" Inch	9" Inch
IP :	IP 65	IP 65
Use Max Conn. :	14 Nos.	14 Nos.
Warranty :	3 Years :	2 Years :

APPLICATION :

- » Uses For Backlit Boxes.
- » Uses For Hordings.
- » Uses For Big Channel
Letters.
- » Use For Glow Sign Board.

